

Secure Connectivity & Superior Productivity

Now available with Ethernet and wireless connectivity



High Speed Printing

With inkjet printing speed up to 10 lines per second, the IJ7100 reduces transaction time, improves teller productivity, leading to greater customer satisfaction.

Ease of Configuration

Compatible with most of the popular core banking software, the IJ7100 can be easily integrated into a bank's operation.

Wireless Connectivity

IP addressable, the IJ7100 offers options to communicate over the Internet. Connectivity is enabled via Ethernet, USB 2.0 or wireless.

Automatic Form Positioning

The IJ7100 aligns forms automatically, so print is consistently in the same location. Ideal for banks that image documents, read rates are better than other competitive models.

Full Length Validation Slot

With its flexible full-length slot, the IJ7100 offers maximum flexibility to print on a wide variety of bank forms—deposit slips, cash tickets, checks and more.

Small Footprint

The IJ7100 is an industry footprint leader. Its compact design lets the IJ7100 teller printer fit onto any teller counter.

Bank Teller Receipt & Validation Printer

The compact and network accessible IJ7100 Receipt and Validation Printer offers banks more control and increased productivity. IP addressable, the IJ7100 enables connectivity via Ethernet, USB 2.0 or wireless. Able to handle a wide range of bank forms with speed

and ease, the IJ7100 is also compatible with most of the popular core banking software. The IJ7100 features a high yield Hewlett-Packard print cartridge and is engineered to deliver proven reliability with a low cost of ownership.

Technical Specifications

Print Method	Thermal inkjet
Ink Cartridges	Part # 95842 (96 x 144 dpi) Part# HP C6602A
Print Speed	5 lines per second at 42 characters / line 10 lines per second at 10 characters / line
Microprocessor	ARM 7
Code Emulations	Epson, IBM, DH, others by request
Connectivity	1 USB 2.0 and 1 Serial RS232 port Wireless IP addressable (option) Ethernet (option)
Serial Baud Rate	9600 or 38400 (dip switch selectable)
Power Source	24 VDC, 1A external power supply

Product Metrics

Overall Dimensions	Width 7.0" x Depth 6.2" x Height 3.6"
With Paper Holder	Width 7.0" x Depth 9.2" x Height 4.6"
Weight	2.9 lb (1.3 kg)
Shipping Weight	4.4 lb (2.0 kg)

Options

Automatic form positioning
Metal tear bar (clear polycarbonate tear bar standard)
Paper roll holder arms (replaces covered roll holder)
Form holder bracket (replaces covered roll holder)

Media

Receipt Paper Roll	Width 3" x Diameter 3" (76mm x 76mm)
Receipt Paper Print Zone	Width 2.75"
Form Size Minimum	Width 5.5"
Form Size Maximum	Width unlimited
Form Print Zone	2.75" wide, top line at 1.54" from form bottom (prints 6 lines above MICR line, 8 lines if no MICR)

Specifications subject to change without notice.
©2017 Addmaster Corporation



Printer shown with roll cover



Printer shown with form rack



Printer shown with roll brackets



Contact us: 888-287-4186
Learn more: blmtechnology.com



ADDMASTER CORPORATION
P.O. Box 5016, Monrovia CA 91017-7116
626.358.2395 Fax 626.358.2784