



Verifone V200c

The Verifone V200c, part of the Verifone Engage portfolio, offers the latest in next-generation features, functionality and versatility. Packed with more speed, an interactive user interface and enhanced security, the V200c is the ideal choice for providing your customers with a unique experience at the point of sale. The V200c leverages the power of Verifone's new architecture, the latest Linux-based operating system and a modern application environment to deliver everything you need in a countertop device and more.

- Color LCD with sound capabilities to drive multimedia usage
- Modern, robust design—ideal for countertop use
- Faster processing to accommodate advanced multimedia usage
- Maximum security and compliance with end-to-end encryption
- Accepts all payment inputs including NFC/CTLS, EMV, and magstripe
- Advanced commerce capabilities available, including BLE/beaconing support



Specifications

Processor

600 MHz, Arm Cortex-A9 32-bit RISC, 1500 MIPS

Memory

384 MB (256 MB Flash, 128 MB SDRAM)

Display

2.8" QVGA, color LCD

Operating System

V/OS (Linux-based)

Connectivity

Dial-up, Ethernet

Printer

30 lps, 40 mm paper roll

Security

PCI PTS 5.X-approved

Card Readers

Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved

Contactless

ISO 14443 Types A and B, ISO 18092-capable, EMVCo L1 certification, MIFARE, supports major NFC/CTLS schemes

Peripheral Ports

2 USB connectors: 1 host, 1 host/client; 1 RS-232-powered

Audio

Buzzer

Power Supply

AC input 100-240 VAC, 50/60 Hz; DC output 11.6 V 1.55 A

Environmental

Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing

Physical

190 mm L x 80 mm W x 70 mm H; 381 g

Other Standard Features

2 SAM slots, backlit keypad

V200c Plus

- Memory: 1024 MB (512 MB Flash, 512 MB SDRAM), microSD
- Connectivity: 5 GHz + 2.4 GHz WiFi, Bluetooth 4.2 BLE
- Audio: Speaker



Contact us: 888-287-4186
Learn more: blmtechnology.com